

97 iso UA2



Gomito con bocchettone piano mf
Union elbow mf, flat seat

DIAMETRO	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
3/8	N09738	14,81	Z09738	18,54	181	140
1/2	N09712	11,69	Z09712	14,76	271	70
3/4	N09734	14,09	Z09734	17,76	422	50
1	N0971	17,76	Z0971	22,60	530	30
1 1/4	N097114	30,51	Z097114	39,36	800	20
1 1/2	N097112	41,35	Z097112	52,21	1000	16
2	N0972	60,11	Z0972	76,14	1550	8
2 1/2	-	-	Z097212	184,65	2610	4
3	-	-	Z0973	247,40	4100	3

guarnizioni per bocchettoni pag. 24.
washers for union pag. 24.

98 iso UA12



Gomito con bocchettone conico mf
Union elbow mf, taper seat

DIAMETRO	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
1/4	N09814	15,53	Z09814	19,16	128	80
3/8	N09838	14,09	Z09838	17,42	160	140
1/2	N09812	11,59	Z09812	14,59	239	70
3/4	N09834	14,76	Z09834	18,54	351	50
1	N0981	20,21	Z0981	25,38	605	30
1 1/4	N098114	33,56	Z098114	42,58	907	20
1 1/2	N098112	41,97	Z098112	52,16	1142	16
2	N0982	68,18	Z0982	86,21	1755	8
2 1/2	N098212	151,44	Z098212	191,56	2800	4
3	N0983	202,63	Z0983	256,83	3500	3

120 iso A1/45°



Gomito 45° ff
Elbow 45° ff

DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
1/4	N12014	7,24	Z12014	9,36	41	400
3/8	N12038	6,85	Z12038	8,42	52	300
1/2	N12012	5,57	Z12012	7,08	84	200
3/4	N12034	6,91	Z12034	8,75	120	120
1	N1201	10,19	Z1201	12,80	180	80
1 1/4	N120114	18,26	Z120114	23,22	286	45
1 1/2	N120112	22,50	Z120112	28,33	414	30
2	N1202	29,28	Z1202	37,02	658	20
2 1/2	N120212	60,44	Z120212	76,41	990	10
3	N1203	59,61	Z1203	75,36	1300	5
4	N1204	176,92	Z1204	249,78	2812	3
6	N1206	473,41	Z1206	669,98	6000	s.c.

121 iso A1/45°



Gomito 45° mf
Elbow 45° mf

DIAMETRO	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
1/4	N12114	5,93	Z12114	7,42	31	500
3/8	N12138	5,30	Z12138	6,63	48	300
1/2	N12112	5,13	Z12112	6,53	74	200
3/4	N12134	6,68	Z12134	8,25	119	150
1	N1211	10,19	Z1211	12,80	204	90
1 1/4	N121114	18,82	Z121114	23,88	314	50
1 1/2	N121112	20,44	Z121112	25,77	436	35
2	N1212	25,89	Z1212	32,62	740	20
2 1/2	N121212	50,37	Z121212	63,78	998	12
3	N1213	62,01	Z1213	78,42	1361	6
4	N1214	194,39	Z1214	271,99	2876	s.c.