





1	iso G4	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Curva lunga 90° mf Long sweep bend 90° mf</p>	1/8	N00118	5,30	Z00118	6,58	40	150	
	1/4	N00114	4,46	Z00114	5,46	60	380	
	3/8	N00138	5,30	Z00138	6,68	80	280	
	1/2	N00112	4,74	Z00112	5,97	130	170	
	3/4	N00134	8,25	Z00134	10,42	205	100	
	1	N0011	11,13	Z0011	14,15	325	40	
	1 1/4	N001114	19,71	Z001114	24,44	555	25	
	1 1/2	N001112	25,38	Z001112	32,34	785	18	
	2	N0012	42,08	Z0012	52,16	1210	9	
	2 1/2	N001212	91,72	Z001212	117,32	2405	4	
	3	N0013	118,82	Z0013	150,43	3550	3	
	4	N0014	215,60	Z0014	273,19	6700	1	
	6	-	-	Z0016	1.310,00	11850	s.c.	

1/a	iso D4	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Curva corta 90° mf Short bend 90° mf</p>	1/4	N001A14	4,35	Z001A14	5,35	40	400	
	3/8	N001A38	4,96	Z001A38	6,19	66	300	
	1/2	N001A12	4,35	Z001A12	5,46	120	200	
	3/4	N001A34	6,80	Z001A34	8,35	166	120	
	1	N001A1	9,02	Z001A1	11,25	274	60	
	1 1/4	N001A114	13,20	Z001A114	16,98	500	40	
	1 1/2	N001A112	19,32	Z001A112	24,44	650	30	
	2	N001A2	34,57	Z001A2	42,80	1122	20	
	2 1/2	N001A212	57,05	Z001A212	72,02	1600	s.c.	
	3	N001A3	86,66	Z001A3	109,53	2546	s.c.	
	4	N001A4	203,07	Z001A4	257,11	5079	s.c.	
	6	N001A6	779,15	Z001A6	1.095,66	11850	s.c.	

2	iso G1	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Curva lunga 90° ff Long sweep bend 90° ff</p>	1/4	N00214	4,79	Z00214	5,80	60	400	
	3/8	N00238	5,13	Z00238	6,68	105	200	
	1/2	N00212	5,46	Z00212	6,75	140	140	
	3/4	N00234	8,47	Z00234	10,47	230	80	
	1	N0021	11,13	Z0021	14,15	355	40	
	1 1/4	N002114	19,77	Z002114	24,55	625	20	
	1 1/2	N002112	24,39	Z002112	30,17	820	15	
	2	N0022	33,63	Z0022	41,91	1595	8	
	2 1/2	N002212	93,28	Z002212	117,93	2435	4	
	3	N0023	117,15	Z0023	148,26	3825	3	
	4	N0024	221,94	Z0024	281,10	6030	1	

2/a	iso D1	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Curva corta 90° ff Short bend 90° ff</p>	1/4	N002A14	5,24	Z002A14	6,46	64	250	
	3/8	N002A38	4,46	Z002A38	5,35	84	240	
	1/2	N002A12	4,13	Z002A12	5,24	114	140	
	3/4	N002A34	5,57	Z002A34	7,19	186	90	
	1	N002A1	8,69	Z002A1	11,13	312	50	
	1 1/4	N002A114	12,92	Z002A114	16,70	530	40	
	1 1/2	N002A112	17,71	Z002A112	22,50	626	30	
	2	N002A2	27,89	Z002A2	36,12	1230	20	
	2 1/2	N002A212	52,43	Z002A212	66,12	1900	s.c.	
	3	N002A3	90,39	Z002A3	114,42	2600	s.c.	
	4	N002A4	190,78	Z002A4	241,64	500	s.c.	
	5	N002A5	542,16	Z002A5	785,88	7710	s.c.	
	6	N002A6	849,19	Z002A6	1.143,31	12500	s.c.	