







180	iso C1	DIAMETRO	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Croce Cross</p>		1/4	N18014	-	Z18014	-	79	60
		3/8	N18038	-	Z18038	-	94	40
		1/2	N18012	-	Z18012	-	145	60
		3/4	N18034	-	Z18034	-	232	40
		1	N1801	-	Z1801	-	362	25
		1 1/4	N180114	-	Z180114	-	534	12
		1 1/2	N180112	-	Z180112	-	726	12
		2	N1802	-	Z1802	-	1136	6
		2 1/2	N180212	-	Z180212	-	1600	3
		3	N1803	-	Z1803	-	2300	4
		4	N1804	-	Z1804	-	4807	3

221	iso Za1	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Distribuzione a gomito Side outlet elbow</p>		3/8	N22138	-	Z22138	-	90	50
		1/2	N22112	-	Z22112	-	95	80
		3/4	N22134	-	Z22134	-	168	50
		1	N2211	-	Z2211	-	236	30
		1 1/4	N221114	-	Z221114	-	454	15
		1 1/2	N221112	-	Z221112	-	522	10
		2	-	-	Z2212	-	839	7

223	iso Za2	DIAMETRO	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Distribuzione a ti Side outlet tee</p>		1/2	N22312	-	Z22312	-	164	120
		3/4	N22334	-	Z22334	-	229	60
		1	N2231	-	Z2231	-	348	30
		1 1/4	N223114	-	Z223114	-	0,510	20
		1 1/2	N223112	-	Z223112	-	0,630	12
		2	N2232	-	Z2232	-	0,930	10

240	iso M2	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Manicotto ridotto ff Reducing socket ff</p>		1/4 1/8	-	-	Z240R1418	-	30	500
		3/8 1/8	N240R3818	-	Z240R3818	-	39	500
		3/8 1/4	N240R3814	-	Z240R3814	-	38	150
		1/2 1/4	N240R1214	-	Z240R1214	-	54	100
		1/2 3/8	N240R1238	-	Z240R1238	-	52	100
		3/4 1/4	N240R3414	-	Z240R3414	-	82	180
		3/4 3/8	N240R3438	-	Z240R3438	-	76	60
		3/4 1/2	N240R3412	-	Z240R3412	-	90	100
		1 1/4	N240R114	-	Z240R114	-	120	40
		1 3/8	N240R138	-	Z240R138	-	112	40
		1 1/2	N240R112	-	Z240R112	-	120	180
		1 3/4	N240R134	-	Z240R134	-	138	150
		1 1/4 3/8	N240R11438	-	Z240R11438	-	180	25
		1 1/4 1/2	N240R11412	-	Z240R11412	-	260	50

240		iso M2		DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Manicotto ridotto ff Reducing socket ff</p>	1 1/4	3/4	N240R11434	-	Z240R11434	-	232	100		
	1 1/4	1	N240R1141	-	Z240R1141	-	218	100		
	1 1/2	1/2	N240R11212	-	Z240R11212	-	289	40		
	1 1/2	3/4	N240R11234	-	Z240R11234	-	272	40		
	1 1/2	1	N240R1121	-	Z240R1121	-	300	80		
	1 1/2	1 1/4	N240R112114	-	Z240R112114	-	312	75		
	2	1/2	N240R212	-	Z240R212	-	310	20		
	2	3/4	N240R234	-	Z240R234	-	452	20		
	2	1	N240R21	-	Z240R21	-	468	50		
	2	1 1/4	N240R2114	-	Z240R2114	-	428	50		
	2	1 1/2	N240R2112	-	Z240R2112	-	520	40		
	2 1/2	1/2	N240R21212	-	Z240R21212	-	599	30		
	2 1/2	1	N240R2121	-	Z240R2121	-	635	15		
	2 1/2	1 1/4	N240R212114	-	Z240R212114	-	742	15		
	2 1/2	1 1/2	N240R212112	-	Z240R212112	-	748	15		
	2 1/2	2	N240R2122	-	Z240R2122	-	700	12		
	3	1	N240R31	-	Z240R31	-	943	12		
	3	1 1/4	N240R3114	-	Z240R3114	-	920	12		
	3	1 1/2	N240R3112	-	Z240R3112	-	1100	12		
	3	2	N240R32	-	Z240R32	-	946	12		
	3	2 1/2	N240R3212	-	Z240R3212	-	1200	8		
	4	1 1/2	N240R4112	-	Z240R4112	-	1230	5		
	4	2	N240R42	-	Z240R42	-	1700	6		
	4	2 1/2	N240R4212	-	Z240R4212	-	1790	6		
	4	3	N240R43	-	Z240R43	-	1922	6		
	6	3	N240R63	-	Z240R63	-	4600	s.c.		
	6	4	N240R64	-	Z240R64	-	4400	s.c.		
	6	5	N240R65	-	Z240R65	-	5900	s.c.		

241		iso N4		DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Nipplo di riduzione mf Reducing bush mf</p>	1/4	1/8	N241R1418	-	Z241R1418	-	10	1000		
	3/8	1/8	N241R3818	-	Z241R3818	-	22	1000		
	3/8	1/4	N241R3814	-	Z241R3814	-	18	200		
	1/2	1/8	N241R1218	-	Z241R1218	-	39	500		
	1/2	1/4	N241R1214	-	Z241R1214	-	34	150		
	1/2	3/8	N241R1238	-	Z241R1238	-	28	300		
	3/4	1/4	N241R3414	-	Z241R3414	-	64	100		
	3/4	3/8	N241R3438	-	Z241R3438	-	56	100		
	3/4	1/2	N241R3412	-	Z241R3412	-	46	200		
	1	1/4	N241R114	-	Z241R114	-	90	200		
	1	3/8	N241R138	-	Z241R138	-	94	60		
	1	1/2	N241R112	-	Z241R112	-	96	220		
	1	3/4	N241R134	-	Z241R134	-	76	250		
	1 1/4	3/8	N241R11438	-	Z241R11438	-	140	40		
	1 1/4	1/2	N241R11412	-	Z241R11412	-	158	100		
	1 1/4	3/4	N241R11434	-	Z241R11434	-	141	120		
	1 1/4	1	N241R1141	-	Z241R1141	-	126	150		
	1 1/2	1/4	-	-	Z241R11214	-	186	100		
	1 1/2	3/8	N241R11238	-	Z241R11238	-	196	110		
	1 1/2	1/2	N241R11212	-	Z241R11212	-	182	90		
	1 1/2	3/4	N241R11234	-	Z241R11234	-	180	90		
	1 1/2	1	N241R1121	-	Z241R1121	-	176	100		
	1 1/2	1 1/4	N241R112114	-	Z241R112114	-	116	150		
	2	3/8	N241R238	-	Z241R238	-	288	56		
	2	1/2	N241R212	-	Z241R212	-	274	60		
	2	3/4	N241R234	-	Z241R234	-	276	55		
	2	1	N241R21	-	Z241R21	-	308	55		
	2	1 1/4	N241R2114	-	Z241R2114	-	302	60		
	2	1 1/2	N241R2112	-	Z241R2112	-	254	80		
	2 1/2	1/2	N241R21212	-	Z241R21212	-	568	30		
	2 1/2	3/4	N241R21234	-	Z241R21234	-	580	30		
	2 1/2	1	N241R2121	-	Z241R2121	-	567	20		
	M	F								

