




2282	PN 16	EN 1092-1 (EX UNI 2282) COLLARINO 11 B									
		CODICE	Dn.	Ø Foro	Ø Est.	Spess.	N. Fori	Inter.	Peso kg.	€/cad.	Bulloni
		K2282015	15	22,5	95	14	4	65	0,73	-	M12x50
		K2282020	20	28	105	16	4	75	1,03	-	M12x50
		K2282025	25	34,5	115	16	4	85	1,24	-	M12x50
		K2282032	32	43,5	140	16	4	100	1,82	-	M16x60
		K2282040	40	49,5	150	16	4	110	2,1	-	M16x60
		K2282050	50	61,5	165	18	4	125	2,81	-	M16x60
		K2282065	65	77	185	18	8	145	3,4	-	M16x60
		K2282080	80	90	200	20	8	160	4,61	-	M16x65
		K2282100	100	115,5	220	20	8	180	4,9	-	M16x65
		K2282125	125	141	250	22	8	210	6,7	-	M16x70
		K2282150	150	170,5	285	22	8	240	8,3	-	M20x75
		K2282200	200	221	340	24	12	295	11,1	-	M20x80
		K2282250	250	275	405	26	12	355	16,3	-	M24x90
		K2282300	300	326	460	28	12	410	21,8	-	M24x90
		K2282350	350	357,5	520	30	16	470	31,7	-	M24x95
		K2282400	400	408,5	580	32	16	525	38,3	-	M27x105
		K2282450	450	459	640	40	20	585	54,5	-	M27x105
		K2282500	500	510	715	44	20	650	61,1	-	M30x110
		K2282600	600	611,5	840	54	20	770	116,5	-	M33x115
		K2282700	700	715	910	36	24	840	87	-	M33x115
		K2282800	800	817	1025	38	24	950	111	-	M36x135
		K2282900	900	918	1125	40	28	1050	129	-	M36x135
		K22821000	1000	1020	1255	42	28	1058	169	-	M39x140

Flange a collare in acciaio S235 per saldatura di testa  
Weldin neck flanges steel S235

6092	PN 10	EN 1092-1 (EX UNI 6092) CIECHE 05 A									
		CODICE	Dn.	Ø Foro	Ø Est.	Spess.	N. Fori	Inter.	Peso kg.	€/cad.	Bulloni
		K6092080	80	-	200	22	4	160	4,61	-	M16x65
		K6092200	200	-	340	26	8	295	16,2	-	M20x80
		K6092250	250	-	395	28	12	350	24,1	-	M20x85
		K6092300	300	-	445	28	12	400	30,8	-	M20x85
		K6092350	350	-	505	26	16	460	39,6	-	M20x85
		K6092400	400	-	565	26	16	515	49,6	-	M22x85
		K6092450	450	-	615	28	20	565	63	-	M22x85
		K6092500	500	-	670	28	20	620	73,3	-	M22x90

Flange cieche in acciaio S235  
Blank flanges steel S235

6093	PN 16	EN 1092-1 (EX UNI 6093) CIECHE 05 A									
		CODICE	Dn.	Ø Foro	Ø Est.	Spess.	N. Fori	Inter.	Peso kg.	€/cad.	Bulloni
		K6093015	15	-	95	14	4	65	0,71	-	M12x50
		K6093020	20	-	105	16	4	75	1,03	-	M12x50
		K6093025	25	-	115	16	4	85	1,22	-	M12x50
		K6093032	32	-	140	18	4	100	1,8	-	M16x60
		K6093040	40	-	150	18	4	110	2,09	-	M16x60
		K6093050	50	-	165	20	4	125	2,87	-	M16x60
		K6093065	65	-	185	20	4	145	3,65	-	M16x60
		K6093080	80	-	200	22	8	160	4,61	-	M16x65
		K6093100	100	-	220	22	8	180	5,65	-	M16x65
		K6093125	125	-	250	24	8	210	8,12	-	M16x70
		K6093150	150	-	285	24	8	240	10,5	-	M20x75
		K6093200	200	-	340	26	12	295	16,2	-	M20x80
		K6093250	250	-	405	32	12	355	25,1	-	M24x90
		K6093300	300	-	460	32	12	410	35,2	-	M24x90
		K6093350	350	-	520	36	16	470	48,2	-	M24x95
		K6093400	400	-	580	38	16	525	63,5	-	M27x105
		K6093450	450	-	640	40	20	585	96,5	-	M27x105
		K6093500	500	-	715	44	20	650	102	-	M30x110
		K6093600	600	-	840	54	20	770	226,5	-	M33x115
		K6093700	700	-	910	48	24	840	236	-	M33x115
		K6093800	800	-	1025	52	24	950	325	-	M36x135
		K6093900	900	-	1125	58	28	1050	437,5	-	M36x135
		K60931000	1000	-	1255	64	28	1170	602	-	M39x140

Flange cieche in acciaio S235  
Blank flanges steel S235

\* Disponibilità materiale 8 giorni data ordine/quotazione a richiesta.