





180	iso C1	DIAMETRO	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Croce Cross</p>		1/4	N18014	-	Z18014	-	79	60
		3/8	N18038	-	Z18038	-	94	40
		1/2	N18012	-	Z18012	-	145	60
		3/4	N18034	-	Z18034	-	232	40
		1	N1801	-	Z1801	-	362	25
		1 1/4	N180114	-	Z180114	-	534	12
		1 1/2	N180112	-	Z180112	-	726	12
		2	N1802	-	Z1802	-	1136	6
		2 1/2	N180212	-	Z180212	-	1600	3
		3	N1803	-	Z1803	-	2300	4
		4	N1804	-	Z1804	-	4807	3

221	iso Za1	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Distribuzione a gomito Side outlet elbow</p>		3/8	N22138	-	Z22138	-	90	50
		1/2	N22112	-	Z22112	-	95	80
		3/4	N22134	-	Z22134	-	168	50
		1	N2211	-	Z2211	-	236	30
		1 1/4	N221114	-	Z221114	-	454	15
		1 1/2	N221112	-	Z221112	-	522	10
		2	-	-	Z2212	-	839	7

223	iso Za2	DIAMETRO	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Distribuzione a ti Side outlet tee</p>		1/2	N22312	-	Z22312	-	164	120
		3/4	N22334	-	Z22334	-	229	60
		1	N2231	-	Z2231	-	348	30
		1 1/4	N223114	-	Z223114	-	0,510	20
		1 1/2	N223112	-	Z223112	-	0,630	12
		2	N2232	-	Z2232	-	0,930	10

240	iso M2	DIAMETRO Ø	CODICE NERO	INDICE NERO	CODICE ZINCATO	INDICE ZINCATO	PESO GRAMMI	QUANTITÀ CONFEZIONE
 <p>Manicotto ridotto ff Reducing socket ff</p>		1/4 1/8	-	-	Z240R1418	-	30	500
		3/8 1/8	N240R3818	-	Z240R3818	-	39	500
		3/8 1/4	N240R3814	-	Z240R3814	-	38	150
		1/2 1/4	N240R1214	-	Z240R1214	-	54	100
		1/2 3/8	N240R1238	-	Z240R1238	-	52	100
		3/4 1/4	N240R3414	-	Z240R3414	-	82	180
		3/4 3/8	N240R3438	-	Z240R3438	-	76	60
		3/4 1/2	N240R3412	-	Z240R3412	-	90	100
		1 1/4	N240R114	-	Z240R114	-	120	40
		1 3/8	N240R138	-	Z240R138	-	112	40
		1 1/2	N240R112	-	Z240R112	-	120	180
		1 3/4	N240R134	-	Z240R134	-	138	150
		1 1/4 3/8	N240R11438	-	Z240R11438	-	180	25
		1 1/4 1/2	N240R11412	-	Z240R11412	-	260	50